

FORTISSIMO

The FORTISSIMO is offered to the following standard alternatives:

- A.** Hull with mounted cast iron keel, deck and superstructure and all other fiberglass reinforced plastic (FRP) details.
- B.** Complete on deck, with main bulkheads, mast pillar and engine installed but no other interior arrangements.
- C.** Complete yacht, but with interior joinery and installations as a complete building kit.
- D.** Complete yacht according to the following specification.

SPECIFICATION

Hull and deck manufactured in handlaid fiberglass reinforced polyester with dimensions in accordance with actual European standards and regulations.

Deck in sandwich construction.

Keel of cast iron with bolts of acidproof stainless steel.

Chainplates and stemfittings of acidproof stainless steel. strongly bolted to brackets and stem.

Rudder of FRP with fittings of acidproof stainless steel med delrin bearings.

Pulpit and stanchions of acidproof stainless steel.

Superstructure and cockpit with coamings and seats in handlaid FRP, roof and cockpit floorboard in sandwich construction. Sliding hatch, garage and sprayhood bow in handlaid FRP. Selfbailing cockpit. Entrance doors and cockpit seats in teak. Four ventilators of fixed Dorade-type of FRP. Cabinwindows of hardened glass with aluminium frames.

Rig with mast och boom in eloxidized aluminium. Standing rigging of 19-wires, acidproof stainless steel cables. Halyards, reefing- and trimlines are drawn to the cockpit with stoppers and geared winches on the coachroof. Geared winches for jib- and spinnakersheets on the cockpit coamings. 6-parts pulley blocks for the main sheet with a trolley on the rail forward of the helmsman. Blocks, trolley and rail for the selftacking jib.

Interior in mahogany. Two berths in the bow, separated from the main cabin through two head compartments.

Cockpit with stowage compartments on both sides. On deck stowage in fore- and aftpeak.

Engine Volvo Penta MD 2020 of 18 hp (13kW) with generator, electric start, fresh water cooling, saildrive and folding propeller. Instruments and controls close to the helmsman. 12V startbattery, 75 lit fuel tank.

Standardequipment includes mainsail, jib, main- and jibsheet. 12 V supporting battery and electric system, lanterns, lamps at pantry, navigation table, main cabin and headcompartment, one lamp at every berth. Freshwater tanks, totally 110 liters, freshwaterpumps at wash and dish basins, the latter also equipped with saltwaterpump. Twoburner, gimballled stove (stove with oven as extras). Head with holding tank. Fireextinguisher. Fixed bailing pump. Flagpolefitting. 2 mooring lines of 10 m. 1 anchor line of 40 m. 1 fishermans anchor of 12 kg. 6 st fenderts.

Prices according to separate pricelist.

Reservations for price- and technical changes without further notifications.